



Wolver AntiFreeze & Coolant WG11 Concentrate

VERPACKUNG

208 L | 60 L | 5 L | 1.5 L

Wolver Antifreeze & Coolant WG11 Concentrate - high quality concentrate coolant for modern gas and diesel engines of cars, trucks, agricultural machinery, stationary engines (including engines of light metals), which operated in all seasonal and climatic conditions.

Wolver Antifreeze & Coolant WG11 Concentrate - protects your engine against freezing, overheating, corrosion, prevents the formation of harmful deposits. It provides reliable protection of the engine metal parts made of cast iron, aluminium, copper and steel.

Wolver Antifreeze & Coolant WG11 Concentrate - produced on the basis of monoethylene glycol and special anti-corrosion additives. Does not contain nitrites, amines, silicates, phosphates and borates.

SPECIFICATIONS: WG11

MEETS THE REQUIREMENTS OF:

ASTM D 3306, D 4985
VW/Audi/Seat/Skoda TL 774-C (G 11),
BMW GS 9400,
MAN 324 NF,
MB 325.0/325.2,
MTU (MTL 5048),
BS 6580,
Porsche,
Saab 6901 599,
Opel GM QL 130100, Cummins 85T8-2,
Cummins CES 14603,,

Caterpillar,
Detroit Diesel 7SE298,
John Deere 8650-5, Case,
New Holland, Volvo, MACK 014617004

Characteristics

- Powerful and long-lasting protection against corrosion for all parts of the cooling system, which consist of materials such as steel, cast iron, aluminum, copper, brass, soft solder
- Maintenance-free frost and overheating protection with a higher boiling point
- Extended coolant life
- Avoidance of cavitation damages, such as on the coolant pump

- Compatibility with varnishes
- Compatibility with hose and sealing materials
- Avoidance of sediments, which can cause radiator plugging
- Avoidance of foaming

Application

Wolver Antifreeze & Coolant WG11 Concentrate should be mixed before pouring into the cooling circuit with water at a concentration of 33 to max. 60 vol% can be used. Applying a 50/50 ratio for the mixture of water and **Wolver Antifreeze & Coolant WG11 Concentrate** is recommended.

Protection against the cold / antifreeze

50 vol% in water -38 ° C

33 vol% in water -18 ° C

Miscibility

To estimate all advantages of **Wolver Antifreeze & Coolant WG11 Concentrate** the mixing with other coolants is not recommended. For the preparation of mixtures preferably softened water should be used.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 20°C	g/cm ³	1,10 - 1,16
Boiling point	°C	> 165
pH-value (50%, 20°C)		7,6
Reserve alkalinity		4,6
Water content	%	max. 5,0
Colour		blue

1,5L - Can	4153	4260360941535
5L - Can	4420	4260360944208
60L - Barrel	4355	4260360943553
208L - Barrel	4432	4260360944321