



## Wolver ATF 6000

### VERPACKUNG

208 L | 20 L | 1 L

**Wolver ATF 6000** - the newest fluid for automatic transmissions based on HC base oils and high-performance additives. The unique composition of the oil provides extended service intervals, excellent resistance to wear and oxidation, efficient operation at the lowest temperatures.

**Wolver ATF 6000** - recommended for use in modern stepped automatic boxes and hydraulic mechanisms for controlling cars, minibuses and trucks.

The performance of **Wolver ATF 6000** covers the requirements of ATF DEXRON IID / DEXRON III F/G/H. Applied base oils and additive packages ensure reliable operation throughout the life of the operation (follow the operating instructions of the equipment manufacturer).

### SPECIFICATIONS

GM DEXRON VI,  
DEXRON IID/DEXRON III F/G/H

### MEETS THE REQUIREMENTS OF

Ford Mercon LV,  
Mercon WSS-M2C138 / CJ/166-H922-  
A1/924-A  
Toyota T III/IV, DII/D III,  
Allison C-4,  
MB 236.1, 236.5, 236.7,  
236.8, 236.9, 236.41,  
JWS 314/9683/3309/3324,  
Nissan Matic C/D/J/K/S  
KIA/Hyundai SP-II/ SP-III/ SP- IV/ SP- IVM/  
SP- IVRR,  
ETL 7045 / 7045E / 8072B /LA 2634 / Mini  
Cooper T- IV  
ATF 5AT/ ATF HP, VW/ VAG G 055-025, G  
052-162

### ***Properties:***

- Extreme wear resistance;
- High resistance to oxidation;

- Improved friction characteristics;
- Excellent low temperature properties, down to -43 ° C;
- Prevents foaming;
- High ability to withstand loads;
- Neutral with respect to sealing materials.

***Efficiency:***

- Provides fuel economy;
- Increases the service life and power of the transmission mechanism;
- Exceptionally reliable operation under extreme conditions;
- Good operability at low temperatures;
- Stability of viscosity also at high loads at high temperatures;
- Year-round use;

***Application:***

- Automatic transmissions of vehicles according to the recommendations of the machinery manufacturers;
- Vehicles with manual gearbox as recommended by the manufacturer;
- For power steering as recommended by the manufacturer;

**Not intended for use in DCT/DSG or CVT transmissions and where an oil with Ford Type F/G specifications is prescribed.**

***Waste management:***

**Wolver ATF 6000** waste oil is classified as Category 2 waste and must be disposed of in designated areas.

***Compatibility:***

**Wolver ATF 6000** is compatible with comparable oils and can be mixed with any of them. In order to take full advantage of **Wolver ATF 6000**, it is recommended to use it without mixing.

***Data table***

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	843
Viscosity at 40°C	cSt	29
Viscosity at 100°C	cSt	6
Viscosity index		157
Flash point COC	°C	204
Pour point	°C	-43
Color		Red