



Wolver Atlantis 2T

VERPACKUNG

208 L | 60 L | 1 L

WOLVER Atlantis 2T is specially designed for all 2-stroke outboard engines developed ashless two-stroke oil that meets NMMA TC-W3.

SPECIFICATIONS

API TC
JASO FC
NMMA TC-W3

MEETS THE REQUIREMENTS OF

SUZUKI
YAMAHA
MERCURY
MARINER
JOHNSON
KAWASAKI
EVINRUDE

Characteristics

- Excellent protection against rust and corrosion
- Can easily be mixed with gasoline
- High wear protection
- Extraordinary lubrication
- High oxidation stability
- Ash-free formula

Effects

- Optimal operating reliability
- Prevents against deposits - spark-plug bridge formation
- Environment-friendly - low smoke formation
- Selfmixing in tank
- Selfmixing and for separate lubrication

Utilization

- All 2-stroke petrol outboard engines, jet skis, Personal Watercraft
- Typical mixture ratio of 1:50 - 2% (Follow manufacturer's recommendation)

Disposal

- **WOLVER Atlantis 2T** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

- **WOLVER Atlantis 2T** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **WOLVER Atlantis 2T** only.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	867
Viscosity at 40°C	cSt	35,9
Viscosity at 100°C	cSt	6,29
Viscosity index		126
Flammpunkt PM	°C	107
Pour point	°C	-30
TBN	mgKOH/g	8,7
Colour		brown

208L - Barel 4041 4260360940415
 1,5L - Can 4145 4260360941450