



## Wolver Gear Oil GL-5 80W-90

### VERPACKUNG

208 L | 60 L | 20 L | 1 L

**WOLVER Gear Oil GL-5 SAE 80W-90** is a hypoid gear oil for mechanical gears based on high-quality, solvent refining basic oils.

**WOLVER Gear Oil GL-5 SAE 80W-90** multi-purpose gear oil: To avoid seasonal change of gear oil WOLVER Gear Oil GL-5 SAE 80W-90 multi-purpose gear oil is available with the viscosity categorie SAE 80W-90 and thus can be applied in winter as well as in summer.

The universal application of **WOLVER Gear Oil GL-5 SAE 80W-90** reduces the risk of confusion and simplifies stockkeeping. The balanced combination of additives guarantees properties like high pressure susceptibility, exceptional good viscosity-temperature behaviour. High oxidation stability, low pour point, good wear protection and avoids black sludge formation.

### SPECIFICATIONS

SAE 80W-90  
API API GL-5

MEETS THE REQUIREMENTS OF  
CLARK FORM ALC-1 5M Rev.7-80 KE, TLC-  
25 3M GAC 4-78,CS 3000 B, EATON  
BULLETIN 6007, 2052, 2053,  
FORD M-2C-9022 A / SM-2C-1011-A / EST-  
M2C-108C,  
FULLER FORM 121,  
JI CASE MS 1316,  
JOHN DEERE JDM J 11D/E, KOMATSU  
DRESSER B22-0003, B22-0005,  
MACK GO-G,

MAN 342 N / 342 Typ M2 (160.000 km.)  
MB 235.0, 235.6, ROCKWELL  
INTERNATIONAL 0-76,  
TEREX EEMS 19003,  
VME AMERICAS EEMS 19003 F, VOLVO  
97310, 97313  
ZF TE-ML 05A,  
07A,08,12E,16B/C/D,17B,19B,21A,  
DAF  
Renault

### Characteristics

- Very well wear protection
- Good sticking and pressure-bursting lubrication film
- First-rate oxidation stability
- Exceptional good viscosity temperature behaviour
- Neutral towards metals and sealing materials
- No foaming

## **Effects**

- Optimal operating properties
- Reduces wear and background noises
- Multi-purpose Hypoid-gear-oil
- Reducing of sorts
- Engine oil for all seasons

## **Utilization**

- Motor vehicle axle drive (differential gear) according API GL 5
- High loaded gear boxes according API GL 5
- Distributors-, intermediary- and auxiliary gearboxes in cars and working machines

## **Disposal**

**WOLVER Gear Oil GL-5 SAE 80W-90** is assigned to category 2 of used oils and thus is free for disposal.

## **Miscibility**

**WOLVER Gear Oil GL-5 SAE 80W-90** gear oil of hypoid range is fully tolerated with comparable lubrications and can be mixed. However, it is recommended to take only **WOLVER Gear Oil GL-5 SAE 80W-90** when refilling.

## **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	871.4
Viscosity at 40°C	cSt	131
Viscosity at 100°C	cSt	15.29
Viscosity index		120
Flash point COC	°C	234
Pour point	°C	-30

1L - Can	4131	4260360941313
4L - Can	4205	4260360942051
20L - Pail	4065	4260360940651
60L - Barrel	4197	4260360941979
208L - Barrel	4035	4260360940354

4197  
4035