



## Wolver Gear Oil GL-5 85W-140

VERPACKUNG

208 L | 20 L

**WOLVER Gear Oil GL-5 85W-140** is a hypoid gear oil for manual transmissions of both passenger cars and trucks and industrial equipment. The possibility of all-season use provides good fluidity at low temperatures and resistance to aging, even at high temperature loads.

**WOLVER Gear Oil GL-5 85W-140** is produced on the basis of a high-quality base oil with the use of a special additive package, which results in: high compressibility, stable viscosity, oxidation resistance, low freezing temperature, good lubrication and cleaning properties.

**WOLVER Gear Oil GL-5 85W-140** can also be used for high-loaded driving bridges with hypoid gearing, where the use of transmission oil of class 85W-140 is recommended by the manufacturer of the equipment.

SPECIFICATIONS:  
SAE 85W-140  
API GL-5

MEETS THE REQUIREMENTS OF:  
MIL L-2105 D, CS 3000 B,  
CLARK FORM ALC-1 5M Rev. 7-80 KE,  
TLC-25 3M GAC 4-78,  
FORD  
M-2C-9002 A/  
SM-2C-1011-A/  
EST-M2C-108C,  
JOHN DEERE JDM  
J 11D/E, KOMATSU DRESSER B22-0003,  
B 22-0005,

MAN 342 M-2 (bi 160 000 km vor dem  
Ölwechsel), MB 235.0, 235.6,  
VOLVO 97310, 97313, ZF TE-ML 05A, 07A,  
08, 12E, 16B, 16C, 16D, 17B, 19B, 21A

### ***Characteristics***

- Excellent wear resistance;
- Exceptional lubricating properties;
- High resistance to oxidation;
- Stable viscosity at high temperatures;
- Prevents foaming;
- Neutral with respect to sealing materials.

### **Effects**

- Optimal working properties;
- Reduces wear and running noise;
- Universality of application;
- Year-round use.

### **Utilization**

- Differentials of leading bridges;
- Heavily loaded mechanical transmission;
- Transfer box, intermediate reducer;
- Auxiliary transmission of cars.

### **Disposal**

**WOLVER Gear Oil GL-5 85W-140** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER Gear Oil GL-5 85W-140** gear oil of hypoid range is fully tolerated with comparable lubrications and can be mixed. However, it is recommended to take only **WOLVER Gear Oil GL-5 85W-140** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	905
Viscosity at 40°C	cSt	387
Viscosity at 100°C	cSt	27,9
Viscosity index		100
Flash point COC	°C	220
Pour point	°C	-18

20L - Pail      4295      4260360942952  
4L - Can      4085      4260360940859