



## Wolver Modelux EP 2

### VERPACKUNG

170 KG | 16 KG | 400 ML

**WOLVER MODELUX EP2** - high anti-wear and extreme pressure grease. It meets the requirements of the automotive industry as a universal automotive lubricants.

**WOLVER MODELUX EP2** - universal lithium grease is recommended for year-round use, as the main lubricant for automotive park and car owners in normal operating conditions.

Operating Temperature Range: -30 ° C ... + 120 ° C

### SPECIFICATIONS

NLGI 2 · KP2K-30 ·  
L-XCCEB 2

### ***Characteristics***

- wear protection at high loads and speeds;
- provides long-term protection against corrosion even under water, snow, dirt and dust influence;
- it provides mechanical and thermal stability;
- reliable sealing mechanism nodes.

### ***Utilization***

- Hub bearings, ball bearings, cardan shaft crosses, steering gear and other chassis components of cars and trucks;
- Accessory mechanisms for automobiles, such as windows, water pump bearings, generator bearings, cables, hinges and locks, slides, winches, etc .;
- Rolling and plain bearings, bushings, shafts, pins and other components of industrial friction, agricultural, lifting and transport, garage and power equipment under normal operating conditions.

### ***Data table***

PROPERTIES	UNIT	TYPICAL INDICATORS
------------	------	--------------------

NLGI grade			2
Penetration at +25° C	DIN ISO 2137	MM·10 <sup>-1</sup>	270
Dropping point	DIN ISO 2176	°C	200
4 Ball test: Wear Test	DIN 50324	MM	0,44
4 Ball test: Weld Point Test	DIN 50324	H	2450