



Wolver Modelux EP 2

VERPACKUNG

170 KG | 16 KG | 400 ML

WOLVER MODELUX EP2 - high anti-wear and extreme pressure grease. It meets the requirements of the automotive industry as a universal automotive lubricants.

WOLVER MODELUX EP2 - universal lithium grease is recommended for year-round use, as the main lubricant for automotive park and car owners in normal operating conditions.

Operating Temperature Range: -30 ° C ... + 120 ° C

SPECIFICATIONS

NLGI 2 · KP2K-30 ·
L-XCCEB 2

Characteristics

- wear protection at high loads and speeds;
- provides long-term protection against corrosion even under water, snow, dirt and dust influence;
- it provides mechanical and thermal stability;
- reliable sealing mechanism nodes.

Utilization

- Hub bearings, ball bearings, cardan shaft crosses, steering gear and other chassis components of cars and trucks;
- Accessory mechanisms for automobiles, such as windows, water pump bearings, generator bearings, cables, hinges and locks, slides, winches, etc .;
- Rolling and plain bearings, bushings, shafts, pins and other components of industrial friction, agricultural, lifting and transport, garage and power equipment under normal operating conditions.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
------------	------	--------------------

NLGI grade			2
Penetration at +25° C	DIN ISO 2137	MM·10 ⁻¹	270
Dropping point	DIN ISO 2176	°C	200
4 Ball test: Wear Test	DIN 50324	MM	0,44
4 Ball test: Weld Point Test	DIN 50324	H	2450