



## WOLVER Multipurpose Gear Oil GL-4 75W-90

### VERPACKUNG

208 L | 60 L | 20 L | 1 L

**WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90** - is a multi-purpose gear oil of viscosity category SAE 75W/90. It is based on semi synthetic ground components and a very shear stable VI-Improver which ensures at long-term the desired SAE-category acc. DIN 51512 also under highest load. Because of its excellent viscosity-temperature behaviour this product can be applied in the fleet round the year.

**WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90** - is suitable for lubrication of gear boxes, differential and steering gears in vehicles where the service instructions prescribe EP gear oil types.

### SPECIFICATIONS

SAE 75W-90  
API GL-4  
SAE 75W-90

### MEETS THE REQUIREMENTS OF

MAN 341 Z-1,  
MB 235.1,  
ZF TE-ML 02A, 16A, 17A, 19A,  
MIL-L-2105 D

### ***Characteristics***

- Very well wear protection
- First-rate oxidation stability
- High lubrication stability
- Excellent viscosity-temperature behaviour
- High pressure susceptibility
- Excellent corrosion protection
- Prevents foaming
- Neutral towards metals and sealing materials

### ***Effects***

- Optimal operating properties
- Reduces wear and background noises
- Excellent cold flow characteristics
- Free-flow up to -45°C

- All-year operation

### **Utilization**

- Motor vehicle gear box
- Motor vehicles differential gear
- Motor vehicles steering gear
- with normal to high load according API GL 4

### **Disposal**

**WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90** gear oil is fully tolerated with comparable lubrications and can be mixed. However, it is recommended to take only **WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	875
Viscosity at 40°C	cSt	82,3
Viscosity at 100°C	cSt	14,47
Viscosity index		184
Flash point COC	°C	234
Pour point	°C	-45

208L - Barrel 4260360942013