



## Wolver Optima GP 2

### VERPACKUNG

170 KG | 16 KG | 400 ML

**WOLVER OPTIMA GP2** - universal multigrade grease for industry and transport.

It has higher heat resistance and water resistance properties compared with traditional lithium greases.

**WOLVER OPTIMA GP2** - universal complex calcium-lithium grease.

Operating temperature range: -30° C ... +150° C

### SPECIFICATIONS

NLGI 2

K2N-30

L-XCEEA 2

### ***Characteristics***

- increase pressure properties and wear resistance;
- high stability at elevated temperatures;
- good adhesion to metal and the seal gaps, waterproof and long-term protection against corrosion;
- reducing the range of used lubricants and cost savings by reducing the inventory of lubricants.

### ***Utilization***

- Wheel bearings and units of chassis, agricultural and building machines and equipment;
- Bearings of industrial and metallurgical equipment in a wide range of loads and speeds up to 5000 rev/ min;
- Bearings and presses components , extruders, conveyors, crushers, gearboxes, agricultural equipment;
- Equipment operating in enclosed areas with high humidity or high dust content;
- Small and household appliances, garage equipment and tools.

### ***Data table***

| PROPERTIES                   |              | UNIT                | TYPICAL INDICATORS |
|------------------------------|--------------|---------------------|--------------------|
| NLGI grade                   |              |                     | 2                  |
| Penetration at +25° C        | DIN ISO 2137 | MM·10 <sup>-1</sup> | 275                |
| Dropping point               | DIN ISO 2176 | °C                  | 250                |
| 4 Ball test: Wear Test       | DIN 50324    | MM                  | 0,39               |
| 4 Ball test: Weld Point Test | DIN 50324    | H                   | 2195               |

20L - Pail      4229      4260360942297  
 208L - Barrel 4230      4260360942303  
 400g -      4012      4260360940125  
 cartridge