



Wolver Rally Special 10W-60

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER Rally Special SAE 10W-60 is a HC-Synthetic engine oil for highly loaded petrol and diesel car engines.

WOLVER Rally Special SAE 10W-60 is ideal for engines which are submitted to hardest conditions in motor sports. With its broad viscosity SAE 10W-60 extremely high temperature stability can be assured.

WOLVER Rally Special SAE 10W-60 fulfils the high quality requirements of all car producers.

SPECIFICATIONS:
SAE 10W-60
API SL/CF/EC
ACEA A3/B3

MEETS THE REQUIREMENTS OF:
VW 501.01, 505.00

Characteristics

- High wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- High cleaning capability
- High oxidation and temperature stability
- Prevents black sludge formation

Effects

- Excellent cold starting behaviour
- Very good operating reliability
- Optimises motor performance
- Optimal engine cleanliness
- Low oil consumption
- High margin of performance and high product stability
- All-year operation

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- CDI- and TDI motors
- Direct-injection

Disposal

- **WOLVER Rally Special SAE 10W-60** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

- **WOLVER Rally Special SAE 10W60** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **WOLVER Rally Special SAE 10W-60** it is recommendable to use only **WOLVER Rally Special SAE 10W-60** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	865
Viscosity at -30°C	cP	6910
Viscosity at 40°C	cSt	184
Viscosity at 100°C	cSt	26,0
Viscosity index		177
Flash point COC	°C	222
Pour point	°C	-36
TBN	mgKOH/g	13