



## Wolver STOU 10W-30, 80W

### VERPACKUNG

208 L | 60 L | 20 L

**WOLVER STOU SAE 10W-30, 80W** - is a special oil which meets the recommendations of all well known tractor manufacturers. It can be used equally for engines, gears and hydraulic systems of modern tractors.

**WOLVER STOU SAE 10W-30, 80W** - high-quality basic oils and selected additives provide a disturbance-free operation of all units at all seasons. Thus also best suitable for wet brakes and clutches (power shaft clutches).

### SPECIFICATIONS

SAE 10W-30, 80W  
API CH-4/CE/SF  
ACEA E3  
HVLP-D 68 (ISO VG 68)  
API GL-4

### MEETS THE REQUIREMENTS OF

ALLISON C-4  
CASE MS 1118/1206/1207/1209/1230  
Denison HF-2  
International Harvester B6  
FIAT AF 87  
CASE NH MAT 3505/3509/3525/3526  
CATERPILLAR TO-2  
DEUTZ DQC I-02

FORD M2C48-C3/M2C-86B/M2C134-D/M2C159B,C  
JOHN DEERE J 27  
MASSEY FERGUSON CMS 1145 (M1135-1145)  
MB-Freigabe 227.1/228.1  
NEW HOLLAND NH 024C/030C/410B/420A  
ZF TE-ML 06A/B/C/F, 07B/D

### ***Characteristics***

- Reduces formation of ageing products at high temperatures
- Neutralizes acids emerging from fuel combustion
- First-rate anti-volatilization behaviour
- High ageing stability
- Excellent viscosity-temperature behaviour

### ***Effects***

- Optimal operating properties
- Provides disturbancefree operation of all engines, gears, hydraulic and brake units
- Good balanced friction behaviour at wet brakes and gears
- All-year operation
- Excellent cold starting behaviour

### **Utilization**

- All kinds of agricultural machines

### **Disposal**

- **WOLVER STOU SAE 10W-30, 80W** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER STOU SAE 10W-30, 80W** is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only **WOLVER STOU SAE 10W-30, 80W** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	871
Viscosity at -30°C	cP	6020
Viscosity at 40°C	cSt	71,0
Viscosity at 100°C	cSt	10,7
Viscosity index		140
Flash point COC	°C	224
Pour point	°C	-48
TBN	mgKOH/g	10,2

60L - Barrel 4200 4260360942006  
20L - Pail 4074 4260360940743  
208L - Barrel 4045 4260360940453