



Wolver STOU 10W-30, 80W

VERPACKUNG

208 L | 60 L | 20 L

WOLVER STOU SAE 10W-30, 80W - is a special oil which meets the recommendations of all well known tractor manufacturers. It can be used equally for engines, gears and hydraulic systems of modern tractors.

WOLVER STOU SAE 10W-30, 80W - high-quality basic oils and selected additives provide a disturbance-free operation of all units at all seasons. Thus also best suitable for wet brakes and clutches (power shaft clutches).

SPECIFICATIONS

SAE 10W-30, 80W
API CH-4/CE/SF
ACEA E3
HVLP-D 68 (ISO VG 68)
API GL-4

MEETS THE REQUIREMENTS OF

ALLISON C-4
CASE MS 1118/1206/1207/1209/1230
Denison HF-2
International Harvester B6
FIAT AF 87
CASE NH MAT 3505/3509/3525/3526
CATERPILLAR TO-2
DEUTZ DQC I-02

FORD M2C48-C3/M2C-86B/M2C134-D/M2C159B,C
JOHN DEERE J 27
MASSEY FERGUSON CMS 1145 (M1135-1145)
MB-Freigabe 227.1/228.1
NEW HOLLAND NH 024C/030C/410B/420A
ZF TE-ML 06A/B/C/F, 07B/D

Characteristics

- Reduces formation of ageing products at high temperatures
- Neutralizes acids emerging from fuel combustion
- First-rate anti-volatilization behaviour
- High ageing stability
- Excellent viscosity-temperature behaviour

Effects

- Optimal operating properties
- Provides disturbancefree operation of all engines, gears, hydraulic and brake units
- Good balanced friction behaviour at wet brakes and gears
- All-year operation
- Excellent cold starting behaviour

Utilization

- All kinds of agricultural machines

Disposal

- **WOLVER STOU SAE 10W-30, 80W** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER STOU SAE 10W-30, 80W is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only **WOLVER STOU SAE 10W-30, 80W** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	871
Viscosity at -30°C	cP	6020
Viscosity at 40°C	cSt	71,0
Viscosity at 100°C	cSt	10,7
Viscosity index		140
Flash point COC	°C	224
Pour point	°C	-48
TBN	mgKOH/g	10,2

60L - Barrel	4200	4260360942006
20L - Pail	4074	4260360940743
208L - Barrel	4045	4260360940453