



## Wolver Super Dynamic 10W-40

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

**WOLVER Super Dynamic SAE 10W-40** is an highly alloyed lightrun petrol and diesel engine oil enabling by its additives, selection of grand oils and its viscosity application an energy-saving operation of car diesel engines.

To guarantee the lowest viscosity of the SAE 10W-range as well as simultaneously a low volatilization loss

**WOLVER Super Dynamic SAE 10W-40** lightrun engine contains full synthetic components meeting the demands of high tech.

### SPECIFICATIONS:

SAE 10W-40  
API SL/CF  
ACEA A3/B3, A3/B4

### MEETS THE REQUIREMENTS OF:

MB 229.1  
VW 505.00, 505.01  
BMW Special  
VOLVO VDS  
MAN 271  
MTU

### ***Characteristics***

- Extreme wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

### ***Effects***

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results

- Reduced fuel consumption
- Optimal engine cleanliness
- Low oil consumption
- All-year operation

### **Utilization**

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- with turbo charging
- Suction diesel
- CDI- HDI- and TDI-motors
- with CDi-technology
- Direct-injection
- with catalyst technology

### **Disposal**

- **WOLVER Super Dynamic SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

- **WOLVER Super Dynamic SAE 10W-40** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **WOLVER Super Dynamic SAE 10W-40** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	862
Viscosity at -30°C	cP	5710
Viscosity at 40°C	cSt	99,8
Viscosity at 100°C	cSt	14.6
Viscosity index		155
Flash point COC	°C	226
Pour point	°C	-35
TBN	mgKOH/g	9.3

1L - Can	4109	4260360941092
4L - Can	4005	4260360940057
5L - Can	4260	4260360942600
20L - Pail	4062	4260360940620
60L - Barrel	4192	4260360941924
208L - Barrel	4032	4260360940323

4062