



Wolver Super Fluid ATF 3000

VERPACKUNG

208 L | 60 L | 1 L

WOLVER Super Fluid ATF 3000 ATF Dexron III H automatic transmission fluid is a development of ATF transmission oils. Carefully selected mineral and HC-Synthetic base oils and modified additive and effective ingredient combinations make the quality of this ATF perfect.

WOLVER Super Fluid ATF 3000 overlaps the requirements of Dexron II D, Dexron III F, Dexron III G ATFs. It is a special transmission oil for use in modern, self-engaging vehicle transmissions.

Outstanding ageing and oxidation stability makes it **WOLVER Super Fluid ATF 3000** suitable for lifetime applications (Note manufacturer's specifications).

SPECIFICATIONS

GM Dexron III-H / III G / III F

MEETS THE REQUIREMENTS OF

ALLISON C-4/TES 389
CATERPILLAR TO-2
CHRYSLER MS-9602, MS-7176
FORD MERCON
FORD M2C 138-CJ, 166-H
MAN 339 Typ Z1 & V1, Z2 & V2
MB 236.1, 236.5, 236.6, 236.7

VOITH 55.6335, 55.6336
VOLVO 97340, 97341
ZF TE-ML 02F, 04D, 09, 11A, 14A, 17C

Characteristics

- Extrem wear protection
- High thermo stability
- Optimum foaming behaviour
- Optimum matched friction behaviour
- High load capacity
- High oxidation stability
- Excellent viscosity-temperature behaviour
- Extreme low pour point
- Neutral towards metals and sealing materials

Effects

- Optimal operating reliability at extreme conditions
- Excellent cold flow qualities
- Best lubrication
- All-year operation
- Reduces kinds by universal property

Utilization

- Passenger car automatic gear
- Passenger car gear box according service instructions
- Passenger car servo steering according service instructions
- Vehicle hydraulic plants according service instructions
- Fluid couplings on vehicles in accordance with manufacturer's specifications
- Hydrodynamic converters on vehicles in accordance with manufacturer's specifications

Not suitable for use in DCT/DSG- or CVT-transmissions

Disposal

WOLVER Super Fluid ATF 3000 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Super Fluid ATF 3000 is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **WOLVER Super Fluid ATF 3000** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	854
Viscosity at 40°C	cSt	35,0
Viscosity at 100°C	cSt	7,3
Viscosity index		180
Flash point COC	°C	210
Pour point	°C	-48
Colour		Red

1L - Can	4129	4260360941290
20L - Pail	4307	4260360943072
208L - Barrel	4048	4260360940484