



Wolver Super Light 10W-40

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER Super Light SAE 10W-40 is an highly alloyed lightrun petrol and diesel engine oil enabling by its additives, selection of grand oils and its viscosity application an energy-saving operation of car diesel engines.

To guarantee the lowest viscosity of the SAE 10W-range as well as simultaneously a low volatilization loss

WOLVER Super Light SAE 10W-40 lightrun engine contains full synthetic components meeting the demands of high tech.

SPECIFICATIONS:

SAE 10W-40
API SN/CF
ACEA A3/B3, A3/B4
ILSAC GF-4

MEETS THE REQUIREMENTS OF:

MB 229.1
VW 501.01, 502.00, 505.00
BMW Special

Characteristics

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

Effects

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results
- Reduced fuel consumption
- Optimal engine cleanliness
- Low oil consumption

- All-year operation

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- with turbo charging
- Suction diesel
- CDI- HDI- and TDI-motors
- with CDi-technology
- Direct-injection
- with catalyst technology

Disposal

- **WOLVER Super Light SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Super Light SAE 10W-40 is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **WOLVER Super Light SAE 10W-40** when refilling.

Data table

| PROPERTIES | UNIT | TYPICAL INDICATORS |
|-------------------------|-------------------|--------------------|
| Specific weight at 15°C | kg/m ³ | 865 |
| Viscosity at -30°C | cP | 5710 |
| Viscosity at 40°C | cSt | 99,8 |
| Viscosity at 100°C | cSt | 14.3 |
| Viscosity index | | 156 |
| Flash point COC | °C | 220 |
| Pour point | °C | -36 |
| TBN | mgKOH/g | 9.0 |

| | | |
|---------------|------|---------------|
| 1L - Can | 4105 | 4260360941054 |
| 4L - Can | 4303 | 4260360940033 |
| 20L - Pail | 4061 | 4260360940613 |
| 60L - Barrel | 4191 | 4260360941917 |
| 208L - Barrel | 4031 | 4260360940316 |