



Wolver Triton WR 2

VERPACKUNG

170 KG | 16 KG | 400 ML

WOLVER TRITON WR 2 - water resistant grease based on anhydrous calcium.

WOLVER TRITON WR 2 - withstands to dirty and salted water washout. It has high plasticity under extremely low temperatures.

Operating Temperature Range: -40 ° C ... + 120 ° C

SPECIFICATIONS

NLGI 2 · K2K-40 ·

L-XDCFA 2

Characteristics

- heavy loads wear resistance;
- lasting protection against corrosion in salt and dirty water;
- high adhesion to metal and excellent joints sealing;
- provides mechanisms protection at extremely low temperatures - down to -40 ° C, in any climate, right up to the Arctic.

Utilization

- Marine vessels mechanisms, water transport and coastal engineering in any climate;
- The cars chassis, heavy forest, agricultural and building machinery, mining machinery and other equipment operating under conditions of water influence, dirt, snow, even under extremely low temperatures;
- Rolling and sliding bearings under heavy loads, low and medium speeds under the influence of dirty and salt water washout;
- Household and small equipment (bicycles, motor blocks, saws, cutting machines) - all year round;
- Rust preventing lubrication for equipment and metalware storage.

Data table

| PROPERTIES | UNIT | TYPICAL INDICATORS |
|------------|------|--------------------|
|------------|------|--------------------|

| | | | |
|------------------------------|--------------|---------------------|--------|
| NLGI grade | | | 2 |
| Penetration at +25° C | DIN ISO 2137 | MM·10 ⁻¹ | 280 |
| Dropping point | DIN ISO 2176 | °C | 150 |
| 4 Ball test: Wear Test | DIN 50324 | MM | 0,6 |
| 4 Ball test: Weld Point Test | DIN 50324 | H | 1960 |
| Rust Test | DIN 51811 | | PASSED |

400g - 4018 4260360940187
 cartridge
 20L - Pail 4235 4260360942358
 208L - Barrel 4236 4260360942365