



Wolver Triton WR2

VERPACKUNG

170 KG | 16 KG | 8 KG | 400 ML

WOLVER TRITON WR 2 - water resistant grease based on anhydrous calcium.

WOLVER TRITON WR 2 - withstands to dirty and salted water washout. It has high plasticity under extremely low temperatures.

Operating Temperature Range: -40 ° C ... + 120 ° C

SPECIFICATIONS

NLGI 2 · K2K-40 ·
L-XDCA 2

Characteristics

- heavy loads wear resistance;
- lasting protection against corrosion in salt and dirty water;
- high adhesion to metal and excellent joints sealing;
- provides mechanisms protection at extremely low temperatures - down to -40 ° C, in any climate, right up to the Arctic.

Utilization

- Marine vessels mechanisms, water transport and coastal engineering in any climate;
- The cars chassis, heavy forest, agricultural and building machinery, mining machinery and other equipment operating under conditions of water influence, dirt, snow, even under extremely low temperatures;
- Rolling and sliding bearings under heavy loads, low and medium speeds under the influence of dirty and salt water washout;
- Household and small equipment (bicycles, motor blocks, saws, cutting machines) - all year round;
- Rust preventing lubrication for equipment and metalware storage.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Viscosity of Oil at 40°C	mm ² /s	109

Penetration at 25°C	10 ⁻¹ ·mm	280
Dropping point	°C	148
Anti-corrosion properties	-	pass
Weld Load 4-Ball	kg	141
Colour	-	green

400g - cartridge	4018	4260360940187
20L - Pail	4235	4260360942358
208L - Barrel	4236	4260360942365