



## Wolver Turbinenöl TD 46

### VERPACKUNG

208 L | 60 L | 20 L

**WOLVER Turbinenöl TD 46** Turbine oil with good anti-corrosion and water-separating behaviour, for the application in gas, water and steam turbines

SPECIFICATIONS  
ISO VG 46

MEETS THE REQUIREMENTS OF  
Voith Turbo,  
DIN 51515-1 (L-TD), Siemens (Turbinenöl)

### **Application**

- Preferably applied in steam, gas and water turbines as well as in turbo compressors with normal thermal load
- Excellent suitability for the lubrication and cooling of bearings
- Very well applicable as pressure transfer agents for controlling and regulating devices
- Application in large and industrial power plants

### **Please Note**

According to the operating conditions, oil change intervals of more than 100,000 h can be achieved.

For turbine devices with gears, which demand a turbine oil with increased load scuffing capacity (FZG<sup>3</sup> 8), the product line **WOLVER Turbinenöl TD 46** is available.

### **Disposal**

- **Wolver TURBINENÖL TD 46** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

- **Wolver TURBINENÖL TD 46** Compressor Oil of VG range is well-tolerated with comparable lubrications and thus can be mixed. However, it is recommendable to use only **Wolver TURBINENÖL TD 46** compressor oil of VG-range when refilling.