



Wolver Turbo Power 15W-40

VERPACKUNG

208 L | 60 L | 20 L

WOLVER Turbo Power 15W-40 is a multigrade engine oil for heavy loaded equipment, with all types of diesel engines, including turbocharged. Especially effective in the technology of previous generations - in off-road, construction, agricultural, where the manufacturer regulates the use of CF-4 oil grade.

WOLVER Turbo Power 15W-40 is made of highly refined base oils and includes complex additive packages that ensure stable operation, especially in high mileage engines. The oil reliably protects engine parts from oxidation, prevents carbon and lacquer formation, and high-quality detergent bags ensure the purity of the piston group.

WOLVER Turbo Power 15W-40

- suitable for modern engines requiring CF-4 oils and for previous generations;
- especially effective in countries with hot climates;
- effectively operates under severe operating conditions.

SPECIFICATIONS:

SAE 15W-40

API CF-4

ACEA E2

MEETS THE REQUIREMENTS OF:

MAN 271

MB 228.1

Volvo VDS

Characteristics

- Provides extended drain intervals;
- High resistance to aging and oxidation;
- Stable viscosity for the entire service life;
- Reduces wear and increases engine life;
- Year-round use;
- Excellent detergent properties.

Effects

- Reduces fuel consumption;
- Increase the efficiency of operation and reduce the overall cost of maintenance;
- Excellent low-temperature pumpability;
- Reduced downtime;
- Minimum wear at high loads on the drive parts;
- Provides clean engine.

Utilization

- In diesel engines of commercial vehicles
- With multivalve technology
- With and without turbocharging
- In diesel engines of light trucks and minibuses

Disposal

WOLVER Turbo Power 15W-40 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Turbo Power 15W-40 is miscible with comparable lubrications. It is recommended to take only **Wolver Turbo Power 15W-40** when refilling.

Data Table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 20°C	kg/m ³	910
Viscosity at 100°C	cSt	13,5
Viscosity index		120
Flash point COC	°C	205
Pour point	°C	-30
TBN	mgKOH/g	8,5

20L - Pail 4311 4260360943119
 60L - Barrel 4322 4260360943225
 208L - Barrel 4312 4260360943126