



Wolver Turbo Super 15W-40

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER Turbo Super SAE 15W-40 is a very high categorized SHPD engine oil, which meets the required European and American emission regulations.

WOLVER Turbo Super SAE 15W-40 is thus recommended for the Euro 2, Euro 3, Euro 4 and Euro 5 motor generation with EGR and/or SCR-technology (not for engines with particulate filter).

WOLVER Turbo Super SAE 15W-40 is a universal multigrade engine oil for all types of heavy duty diesel engines. Used for any, even extreme operating conditions. Meets the requirements of extended drain intervals (please observe maintenance manual).

SPECIFICATIONS

SAE 15W-40
API CI-4/SL+SHPD
ACEA A3/B4, E7

MEETS THE REQUIREMENTS OF

MB 228.3, 229.1
MAN M 3275
Volvo VDS-3
Mack EO-M Plus
Cummins CES 20071, 72, 76, 77, 78

MTU 2

IVECO
Renault RVI RLD
Caterpillar ECF-1
Allison C-4
Voith Retarder Typ A

Characteristics

- High flushing effect that eliminates the formation and carbon deposit in the combustion chamber
- Prevents formation of sediment and sludge in engines and oil pan
- Optimal protection against corrosion, oxidation, wear and foaming
- Extremely high pressure stability
- Perfect cleaning capability
- Excellent ageing stability
- Excellent viscosity-temperature behaviour

Effects

- High operating reliability

- Ideal for heavy duty operating conditions
- Suitable for prolonged drain intervals
- Prevents black sludge formation
- Protection against reflector surface formation
- Improved economy due to extended service intervals
- Minimum wear at highly strained engines
- High stable viscosity index
- Multigrade operation

Application

- Commercial vehicle diesel engines
- Turbo charged
- With catalyst technology
- EGR technology
- SCR technology
- Passenger car diesel engines
- Four-stroke gas engines

Utilization

- **WOLVER Turbo Super SAE 15W-40** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

- **WOLVER Turbo Super SAE 15W-40** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **WOLVER Turbo Super SAE 15W-40** only.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	869
Viscosity at -30°C	cP	6040
Viscosity at 40°C	cSt	98,8
Viscosity at 100°C	cSt	14,3
Viscosity index		150
Flash point COC	°C	222
Pour point	°C	-36
TBN	mgKOH/g	10,5

1L - Can	4121	4260360941214
4L - Can	4123	4260360941238
5L - Can	4183	4260360941832
20L - Pail	4064	4260360940644
208L - Barrel	4034	4260360940347