



Wolver Turbo Truck 10W-40

VERPACKUNG

208L | 60 L | 20L

WOLVER Turbo Truck 10W-40 is a HC-Synthetic high performance motor oil for diesel engines of the newest generation. It was specially developed for diesel engines with EURO 5 and EURO 6 standard with after treatment of exhaust gas (particle separator). In order to maintain the functionality after treatment systems and to avoid disturbance, the use of a motor oil with Low SAPS (Low Ash) technology is obligatory.

WOLVER Turbo Truck 10W-40 can also be used for diesel engines with Euro 4 and engines with particulate filters in combination with low-sulfur diesel (up to 50 ppm). The reduced values of sulphate, phosphor and sulphur are guaranteed by selection of especially developed basic oils and additives.

WOLVER Turbo Truck 10W-40 has been developed for use in highly charged diesel motors of commercial vehicles in different operating conditions. Being a UHPD oil, it allows largest intervals of oil change (up to 100.000 km - depending on manufacturer recommendations) and can be used in all trucks, construction machines, busses, agricultural vehicles, etc.

SPECIFICATIONS

SAE 10W-40
API CI-4 + UHPD
ACEA E6-, E7-, E9-08

MEETS THE REQUIREMENTS OF

MB-228.51, (226.9)
MAN M 3477, M 3271-1
VOLVO VDS-3 , CNG CATERPILLAR ECF-1a
CUMMINS CES 20076/77
DAF Long drain
DEUTZ DQC-IV-10 LA
JASO DH-2
MACK EO-N / EO-M Plus
MTU Typ 3.1
RVI (Renault) RLD-2, RXD, RGD
SCANIA Low Ash

Characteristics

- Low Saps (Low Ash) technology

- Highest wear protection
- Exceptional ageing and oxidation stability
- Reduces formation of ageing products at high temperatures
- Low volatilization tendency
- Excellent viscosity-temperature behaviour
- Excellent lubrication in range of highest temperatures

Effects

- Especially for the latest EURO 5 and EURO 6 engine generation
- Improved economy viability by extended inspections-intervals (up to 100.000 km)
- Fuel efficiency by lightrun properties
- Minimum wear at highly strained engines
- All-year operation
- Protection against reflector surface formation
- Guarantee for absolutely clean motors and particle separators.

Utilization

- Commercial vehicle diesel engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- with particulate filter

Disposal

WOLVER Turbo Truck 10W-40 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Turbo Truck 10W-40 is miscible with comparable lubrications. It is recommended to take only **Wolver Turbo Truck 10W-40** when refilling.

Data Table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	860
Viscosity at -25°C	cP	6600
Viscosity at 40°C	cSt	92,8
Viscosity at 100°C	cSt	14,8
Viscosity index		167
Flash point COC	°C	228
Pour point	°C	-33
TBN	mgKOH/g	9,9

20L - Pail 4187 4260360941870

208L - Barrel 4186 4260360941863