



## Wolver UltraTec Longlife III 5W-30

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

**WOLVER UltraTec Longlife III SAE 5W30** is a new long-life III synthesis, high-performance, smooth-running engine oil based on the latest technology.

**WOLVER UltraTec Longlife III SAE 5W30** was especially developed for the petrol and diesel engines of the VW group, with extended maintenance interval conditions (WIV 3 systems), incl. pump-injector engines.

**WOLVER UltraTec Longlife III SAE 5W30** Engine oil of the SAE class 5W/30 is suitable for oil change intervals of up to 50,000 km or 2 years. (See car manufacturer's specifications).

This high performance engine oil can also be used in other types of VW engines, except R5-, V10 TDi pump-injection engines with and without DPF diesel particle filter, which require the VW specifications 503.00, 506.00, 506.01.

### SPECIFICATIONS:

SAE 5W-30  
API SN/CF/EC  
ACEA C3, A3/B4

### MEETS THE REQUIREMENTS OF:

VW 504.00, 507.00  
VW 500.00, 501.00,  
501.01, 502.00, 503.00, 503.01, 505.00,  
505.01, 506.00, 506.01

### ***Characteristics***

- Extreme wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Considerable wear reduction on cylinder and camshaft
- High oxidation and temperature stability
- Low volatilization loss
- Very high cleaning capability
- Particularly low emission combustion

### ***Effects***

- Reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission
- Light motor running
- Optimal engine cleanliness
- Very low resistance on motor starting
- Very good operating reliability
- High margin of performance
- Extended oil change intervals
- All-year operation

### **Utilization**

- VW high-performance and normal four-stroke petrol engines motors with and without WIV-systems
- with multivalve-technology
- with turbo charging
- with catalyst technology
- with extended oil change interval
- VW diesel engines with and without WIV-systems
- with pump and nozzle engines
- with diesel particle systems(DPF)
- with turbo charging
- with catalyst technology

### **Disposal**

- **WOLVER UltraTec Longlife III SAE 5W-30** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER UltraTec Longlife III SAE 5W-30** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **WOLVER UltraTec Longlife III SAE 5W-30** it is recommendable to use only **WOLVER UltraTec Longlife III SAE 5W-30** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	855
Viscosity at -30°C	cP	4730
Viscosity at 40°C	cSt	64,00
Viscosity at 100°C	cSt	11,50
Viscosity index		176
Flash point COC	°C	230
Pour point	°C	-45
TBN	mgKOH/g	6,7
Sulphate ashes	%	0,67