



Wolver Unilux MP2

VERPACKUNG

170 KG | 16 KG | 8 KG | 400 ML

WOLVER UNILUX MP2 - universal multigrade grease for industry and transport.

It has higher heat resistance and water resistance properties compared with traditional lithium greases.

WOLVER UNILUX MP2 - universal complex calcium-lithium grease.

Operating temperature range: -30° C ... +150° C

SPECIFICATIONS

NLGI 2

K2N-30

L-XCEEA 2

Characteristics

- increase pressure properties and wear resistance;
- high stability at elevated temperatures;
- good adhesion to metal and the seal gaps, waterproof and long-term protection against corrosion;
- reducing the range of used lubricants and cost savings by reducing the inventory of lubricants.

Utilization

- Wheel bearings and units of chassis, agricultural and building machines and equipment;
- Bearings of industrial and metallurgical equipment in a wide range of loads and speeds up to 5000 rev/ min;
- Bearings and presses components , extruders, conveyors, crushers, gearboxes, agricultural equipment;
- Equipment operating in enclosed areas with high humidity or high dust content;
- Small and household appliances, garage equipment and tools.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Viscosity of Oil at 40°C	mm ² /s	104
Penetration at 25°C	10 ⁻¹ ·mm	280
Dropping point	°C	242
Anti-corrosion properties	-	pass
Weld Load 4-Ball	kg	237
Colour	-	brown

20L - Pail	4229	4260360942297
208L - Barrel	4230	4260360942303
400g -cartridge	4012	4260360940125