



Wolver UTTO 80W, ISO VG 46

VERPACKUNG

208 L | 60 L | 20 L

WOLVER UTTO is a first-rate multigrade oil and can be used for farm tractors, forklift trucks of all manufacturers as hydraulic and gear oil.

It is suitable for units with wet brakes and clutches (neck shaft coupling).

SPECIFICATIONS

SAE 80W, ISO VG 46
API GL-4
HLP-D/HVLP-D (ISO VG 46-68)

MEETS THE REQUIREMENTS OF

DENISON HF-0, HF-1, HF-2
SPERRY VICKERS I-286-S, M-2950-S
ALLISON C4,
MIL-L-2105,
CATERPILLAR TO-2,
ZF TE-ML 05F, 17E
ALLISON C3,
CASE MS-1204, MS-1205, MS-1206, MS-1207, MS-1209, MS-1210

CASE NEW HOLLAND MAT 3525, 3505
DEUTZ Hydr. Trans Fluid
DENISON HF 1/2/3
JOHN DEERE J 20C/D
MASSEY FERGUSON M-1110, M-1127 A, B;
M-1129 A; M-1135; M-1139; M-1141; M-1143; M-1145
VALMET/VOLVO BM
ZF TE-ML 03E/06

Characteristics

- Excellent viscosity-temperature behaviour
- Excellent detergent- and dispersant characteristics
- High viscosity index
- Good anti-foaming behaviour
- Excellent wear and corrosion protection
- High ageing stability

Effects

- Affords an undisturbed operation of gears, hydraulic and brake systems
- Low pour point
- All-year operation

Utilization

- Gears, back axles, immersion brakes of tractors and fork lift trucks.
- Moving hydraulic systems such as cranes, branch clutches, power steering.
- Axles and hypoid tractor clutches according to API GL 4
- Forestry and construction machinery

Disposal

- **WOLVER UTTO** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER UTTO is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only **WOLVER UTTO** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	871
Viscosity at 40°C	cSt	65,12
Viscosity at 100°C	cSt	10,94
Viscosity index		160
Flash point COC	°C	226
Pour point	°C	-42
ISO VG class		46/68
SAE class		10W/30
TBN	mgKOH/g	-