



## Wolver UTTO 80W, ISO VG 46

### VERPACKUNG

208 L | 60 L | 20 L

**WOLVER UTTO** - is a first-rate multigrade oil and can be used for farm tractors, forklift trucks of all manufacturers as hydraulic and gear oil.

**WOLVER UTTO** - is suitable for units with wet brakes and clutches (neck shaft coupling).

**The product is not intended for use as an engine oil.**

### SPECIFICATIONS

SAE 80W, ISO VG 46  
API GL-4  
HLP-D/HVLP-D (ISO VG 46-68)

### MEETS THE REQUIREMENTS OF

DENISON HF-0, HF-1, HF-2  
SPERRY VICKERS I-286-S, M-2950-S  
ALLISON C4,  
MIL-L-2105,  
CATERPILLAR TO-2,  
ZF TE-ML 05F, 17E  
ALLISON C3,  
CASE MS-1204, MS-1205, MS-1206, MS-1207, MS-1209, MS-1210

CASE NEW HOLLAND MAT 3525, 3505  
DEUTZ Hydr. Trans Fluid  
DENISON HF 1/2/3  
JOHN DEERE J 20C/D  
MASSEY FERGUSON M-1110, M-1127 A, B;  
M-1129 A; M-1135; M-1139; M-1141; M-1143; M-1145  
VALMET/VOLVO BM  
ZF TE-ML 03E/06

### Characteristics

- Excellent viscosity-temperature behaviour
- Excellent detergent- and dispersant characteristics
- High viscosity index
- Good anti-foaming behaviour
- Excellent wear and corrosion protection
- High ageing stability

### Effects

- Affords an undisturbed operation of gears, hydraulic and brake systems
- Low pour point
- All-year operation

### **Utilization**

- Gears, back axles, immersion brakes of tractors and fork lift trucks.
- Moving hydraulic systems such as cranes, branch clutches, power steering.
- Axles and hypoid tractor clutches according to API GL 4
- Forestry and construction machinery

### **Disposal**

- **UTTO** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER UTTO** is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only **WOLVER UTTO** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	871
Viscosity at 40°C	cSt	65,1
Viscosity at 100°C	cSt	10,9
Viscosity index		160
Flash point COC	°C	226
Pour point	°C	-42
ISO VG class		46/68
SAE class		80W/85W

20L - Pail	4073	4260360940736
60L - Barrel	4199	4260360941993
208L - Barrel	4044	4260360940446