



## Wolver ATF Type A

### VERPACKUNG

208 L | 20 L | 1 L

**Wolver ATF Type A** - is a special oil for automatic transmissions, torque converters, hydraulic couplings and power steering systems. It can also be used in the ICIE, according to the recommendations of manufacturer that regulates the use of this type of transmission fluid.

**Wolver ATF Type A** - has improved antioxidant properties, is resistant to foaming and provides increased protection against wear.

Excellent stability and oxidation resistance makes **Wolver ATF Type A** an excellent oil for the entire life cycle (follow the manufacturer's instructions for use).

### SPECIFICATIONS

GM Type A, Suffix A

### MEETS THE REQUIREMENTS OF

Allison C-3 / C-4,  
MB 236.2,  
Caterpillar TO-2,  
Voith DIWA

### Properties:

- High wear resistance;
- High resistance to oxidation;
- Excellent low temperature properties, down to -40 ° C;
- Prevents foaming;
- High ability to withstand loads;
- Neutral with respect to sealing materials.

### Efficiency:

- Contains the transmission mechanism clean;
- Increases the life of the transmission mechanism;
- Extremely reliable operation in severe conditions;
- Good operability at low temperatures;
- Year-round use;

**Applicatio:**

- Automatic car transmissions and torque converters;
- Step-by-step gearboxes for which the ATF is prescribed;
- Hydraulic systems and steering mechanisms.

**Waste management**

**Wolver ATF Type A** waste oil is classified as Category 2 waste and must be disposed of in designated areas.

**Compatibility**

**Wolver ATF Type A** is compatible with comparable oils and can be mixed with any of them. In order to take full advantage of the **Wolver ATF Type A**, it is recommended to use it without mixing.

**Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	870
Viscosity at 40°C	cSt	38
Viscosity at 100°C	cSt	7.6
Viscosity index		167
Flash point COC	°C	205
Pour point	°C	-40
Color		Red