



# Wolver Antifreeze & Coolant Ready to Use WG11

VERPACKUNG 208 L | 10 L | 5 L | 1.5 L

**Wolver Antifreeze & Coolant WG11 Ready to Use** high quality coolant for modern gas and diesel engines of cars, trucks, agricultural machinery, stationary engines (including engines of light metals), which operated in all seasonal and climatic conditions.

**Wolver Antifreeze & Coolant WG11 Ready to Use** - protects your engine against freezing, overheating, corrosion, prevents the formation of harmful deposits. It provides reliable protection of the engine metal parts made of cast iron, aluminium, copper and steel.

**Wolver Antifreeze & Coolant WG11 Ready to Use** produced on the basis of monoethylene glycol and special anticorrosion additives. Does not contain nitrites, amines, silicates, phosphates and borates.

SPECIFICATIONS: WG 11

#### MEETS THE REQUIREMENTS OF:

ASTM D3306 / D4656 / D4985 VW/Audi/Seat/Skoda TL 774-C (G 11), BMW GS 9400, MAN 324 NF, MB 325.0/325.2, MTU (MTL 5048), BS 6580, Porsche, Saab 6901 599, Opel GM QL 130100, Cummins 85T8-2,

Cummins CES 14603, Caterpillar, Detroit Diesel 7SE298, John Deere 8650-5, Case, New Holland, Volvo, MACK 014617004

## **Characteristics**

- Powerful and long-lasting protection against corrosion for all parts of the cooling system, which consist of materials such as steel, cast iron, aluminum, copper, brass, soft solder
- Maintenance-free frost and overheating protection with a higher boiling point
- Extended coolant life
- Avoidance of cavitation damages, such as on the collant pump
- Compatibility with varnishes
- Compatibility with hose and sealing materials

- Avoidance of sediments, which can cause radiator plugging
- Avoidance of foaming

#### **Application**

Wolver Antifreeze & Coolant WG11 Ready to Use it is ready to use product that has been premixed. Do not mix different types of Antifreezes. The ready to use Wolver Antifreeze & Coolant WG11 can be added to your coolant system directly from the can.

### **Miscibility**

To estimate all advantages of **Wolver Antifreeze & Coolant WG11 Ready to Use** the mixing with other coolants is not recommended. For the preparation of mixtures preferably softened water should be used.

## <u>Data table</u>

PROPERTIES	UNIT	TYPICAL INDICATORS
Relative density at 15.6 °C	kg/m³	1071
рН	-	8.4
Freezing point	°C	-38
Colour	-	blue

20L - Pail	4262	4260360942624
208L - Barrel	4263	4260360942631