



## Wolver Ecotec 0W-20

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER Ecotec SAE 0W-20 is a full synthetic low friction engine oil of the latest generation. The exceptional qualities fulfil modern OEM requirements and application conditions. It is optimally coordinated for prolonged oil change intervals.

WOLVER EcoTec SAE 0W-20 is especially suitable for use in passenger petrol and diesel engines with subsequent exhaust treatment systems (DPF), which require engine oils with a low viscosity according to the OEM manual. The newest formula protects the engine as well as the catalytic converter system.

### SPECIFICATIONS:

SAE 0W-20  
API SP (RC)  
ILSAC: GF-6A

### MEETS THE REQUIREMENTS OF:

MB 229.71  
MB 229.72  
BMW Longlife-17 FE+  
GM DEXOS 1 GEN 2  
GM 6094M  
Ford WSS-M2C947-A  
Ford WSS-M2C947-B1  
Ford WSS-M2C962-A1  
Jaguar Land Rover STJLR.03.5006  
Opel / Vauxhall OV0401547  
Volvo VCC RBS0-2AE  
Fiat 9.55535-GSX  
Chrysler MS-12145

| PROPERTIES                    | UNIT               | TYPICAL INDICATORS |
|-------------------------------|--------------------|--------------------|
| Kinematic viscosity at 100 °C | mm <sup>2</sup> /s | 8,16               |
| Viscosity index               | -                  | 163                |
| Pour point                    | °C                 | -42                |
| Viscosity CCS at -30 °C       | mPa·s              | 6200               |
| TBN                           | mgKOH/g            | 7,33               |

|                    |                   |     |
|--------------------|-------------------|-----|
| Flash point        | °C                | 230 |
| Density at 15.6 °C | kg/m <sup>3</sup> | 848 |