



## Wolver Ecotec 5W-30

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER Ecotec SAE 5W-30 is a synthetic low friction engine oil of the latest generation. The exceptional qualities fulfil modern OEM requirements and application conditions. It is optimally coordinated for prolonged oil change intervals.

WOLVER Ecotec SAE 5W-30 is especially suitable for use in passenger petrol and diesel engines with subsequent exhaust treatment systems (DPF), which require engine oils with a low viscosity according to the OEM manual. The newest formula protects the engine as well as the catalytic converter system.

### SPECIFICATIONS:

SAE 5W-30  
API SP/CF  
ILSAC: GF-6A

### MEETS THE REQUIREMENTS OF:

GM DEXOS 1 GEN 2  
GM 4718M  
GM 6094 M  
Ford WSS-M2C946-A  
Ford WSS-M2C946-B1  
Ford WSS-M2C929-A  
CHRYSLER MS-6395  
FIAT 9.55535-CR1

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	10,18
Viscosity index	-	171
Pour point	°C	-42
Viscosity CCS at -30 °C	mPa·s	5500
TBN	mgKOH/g	7,5
Flash point	°C	230
Density at 15.6 °C	kg/m <sup>3</sup>	855