



## Wolver Fenix XHP2

### VERPACKUNG

170 KG | 16 KG | 8 KG | 400 ML

**WOLVER FENIX XHP 2** - high-premium grease based on calcium sulfonate and synthetic components.

**WOLVER FENIX XHP 2** - used primarily at extremely high temperatures and loads. It has extremely high anti-corrosion and water-resistant properties. According to the main parameters considerably exceed the properties of lithium and complex greases.

Operating Temperature Range: -25 ° C ... + 200 ° C

### SPECIFICATIONS

NLGI 2 · KP2S-25 ·  
L-XBGF 2 · LB/GC

### Characteristics

- ensures efficient lubrication, high thermal and antioxidant stability and low oil separation at high temperatures;
- exceptional extreme pressure and anti-wear performance under heavy and shock loads;
- high resistance against corrosion, water and steam washout, destruction resistance under mechanical shifting forces and dirty water influence;
- increased lubrication service intervals and reducing maintenance costs.

### Utilization

- Roll stands mechanisms and drive gear axis of hot rolling steel mills, continuous casting machines;
- Mechanisms and fittings for boilers, furnace and autoclaves;
- Cement, chemical and glass industries equipment, operating under high temperatures. The mechanisms and nodes of road-building machinery and heavy vehicles, vibrating screens of the asphalt plants, heavy loaded bearings in heavy industry;
- Bearings for Paper and Pulp industry equipment, bearings and equipment components used for gas concrete production, drills and hammers;
- Electric motor bearings of large dimensions.

### Data table

| PROPERTIES                | UNIT                 | TYPICAL INDICATORS |
|---------------------------|----------------------|--------------------|
| Viscosity of Oil at 40°C  | mm <sup>2</sup> /s   | 456                |
| Penetration at 25°C       | 10 <sup>-1</sup> ·mm | 285                |
| Dropping point            | °C                   | 306                |
| Anti-corrosion properties | -                    | pass               |
| Weld Load 4-Ball          | kg                   | 447                |
| Colour                    | -                    | red                |

|                   |      |               |
|-------------------|------|---------------|
| 400ml - cartridge | 4020 | 4260360940200 |
| 10L- pail         | 4386 | 4260360943867 |
| 20L - pail        | 4237 | 4260360942372 |
| 208L - barel      | 4238 | 4260360942389 |

4260360943867