



## Wolver Four Stroke Power 4T 10W-30

### VERPACKUNG

208 L | 60 L | 1 L

**Wolver Four Stroke Power 4T 10W-30** - is a universal semisynthetic oil for use in modern four-stroke gasoline and diesel engines of power equipment: generators, water pumps, cultivators, soil cutters, tractors, snow blowers, lawn mowers. It is used in 4T engines of motorcycles, ATVs, scooters and other equipment, according to the manufacturer's recommendations.

**Wolver Four Stroke Power 4T 10W-30** - ideal for modern high-speed 4T engines as well as engines with extended intervals of continuous operations. Thanks to a special package, oil provides easy start-up of your equipment even at negative temperatures.

**Wolver Four Stroke Power 4T 10W-30** - meets the technical requirements of the world's manufacturers of equipment and is suitable for all 4-stroke diesel and gas engines.

SPECIFICATIONS  
SAE 10W-30  
API SL/CF

MEETS THE REQUIREMENTS OF:  
JASO MA2

### **Properties**

- High wear protection
- Unusual resistance to aging and oxidation
- Extreme resistance to high temperatures
- High lubricity
- Provides engine cleanliness
- Low volatility

### **Efficiency**

- High reliability
- Excellent performance at cold start - fast arrival to lubrication points
- Prevents deposition of carbon deposits
- Fuel economy due to improved antifriction properties
- Year-round application

- Ability to use in motorsport

### **Application**

- Modern engines of 4-stroke motorcycles
- Modern engines of 4-stroke power technology

### **Waste management**

- Used Wolver Four Stroke Power 4-T 10W-30 waste oil is classified as Category 2 waste and must be disposed of in designated areas.

### **Compatibility**

**Wolver Four Stroke Power 4-T 10W-30** is fully compatible with similar oils and can be mixed if necessary. In order to fully take advantage of the Wolver Four Stroke Power 4-T 10W-30, it is still recommended to use it without mixing.

### **Data table**

<b>PROPERTIES</b>	<b>UNIT</b>	<b>TYPICAL INDICATORS</b>
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	10.2
Viscosity index	-	140
Pour point	°C	-34
Viscosity CCS at -25°C	mPa·s	6800
TBN	mgKOH/g	6.3
Flash point	°C	216
Density at 15.6 °C	kg/m <sup>3</sup>	877

1L - 4260360943379