



Wolver Four Stroke Racing 4T 10W-40

VERPACKUNG

208 L | 60 L | 1 L

Wolver Four Stroke Racing 4T SAE 10W-40 - is special high performance semisynthetic oil elaborated for modern four stroke engines of motorcycles and small machinery.

Wolver Four Stroke Racing 4T SAE 10W-40 - satisfies the technical demands of all motorcycle manufacturers, and is suitable for all air-cooled and water-cooled 4-stroke motorcycle engines.

SPECIFICATIONS

SAE 10W-40

API SL

MEETS THE REQUIREMENTS OF:

JASO MA-2

Properties

- High wear protection
- Unusual resistance to aging and oxidation
- Extreme resistance to high temperatures
- High lubricity
- Provides engine cleanliness
- Low volatility

Efficiency

- High reliability
- Excellent performance at cold start - fast arrival to lubrication points
- Prevents deposition of carbon deposits
- Fuel economy due to improved antifriction properties
- Year-round application
- Ability to use in motorsport

Application

- Modern engines of 4-stroke motorcycles
- Modern engines of 4-stroke power technology

Waste management

Used **Wolver Four Stroke Racing 4-T 10W-40** waste oil is classified as Category 2 waste and must be disposed of in designated areas.

Compatibility

Wolver Four Stroke Racing 4-T 10W-40 is fully compatible with similar oils and can be mixed if necessary. In order to fully take advantage of the **Wolver Four Stroke Racing 4-T 10W-40**, it is still recommended to use it without mixing.

Data table

| PROPERTIES | UNIT | TYPICAL INDICATORS |
|-------------------------------|--------------------|--------------------|
| Kinematic viscosity at 100 °C | mm ² /s | 13.7 |
| Viscosity index | - | 153 |
| Pour point | °C | -34 |
| Viscosity CCS at -25°C | mPa·s | 6400 |
| TBN | mgKOH/g | 6.2 |
| Flash point | °C | 215 |
| Density at 15.6 °C | kg/m ³ | 878 |

1L - Can 4125 4260360941252
208L - Barel 4042 4260360940422