



Wolver Gear Oil GL-5 / GL-4 80W-90

VERPACKUNG

208 L | 20 L | 1 L

Wolver Universal Gear Oil 80W-90 is a all-season gear oil with excellent anti-friction properties and is based on synthetic components. Unlike traditional transmission oils can be used multifunctionally.

Wolver Universal Gear Oil 80W-90 - thanks to a special combination of additives, high gear efficiency and reduced fuel consumption have been achieved. The oil has an unusually high resistance to oxidation and to temperature changes.

Wolver Universal Gear Oil 80W-90 - designed specifically for mechanical gearboxes and rear axles of cars, light and heavy trucks according to API GL 4 / GL 5. Ideal for universal use in mixed fleets - trucking enterprises, service stations, agricultural producers.

SPECIFICATIONS

SAE 80W-90
API GL-5 / GL-4

MEETS THE REQUIREMENTS OF

MACK GO-j,
MAN 341 Type Z2 / E2,
3343 Type M, 342 Type M2,
MB 235.0, MF 1134,
SCANIA STO 1: 0, 2: 0,
VOLVO 97310, 97312,
ZF TE-ML 02B, 05A, 07A, 08.12E, 16B, 16C,
16D, 17B, 19B, 21A
MIL PRF-2105 E/L 2105 A, B, C, D, E

Properties

- Excellent wear resistance;
- Effective protection against oxidation and high temperatures;
- Exceptional viscosity-temperature characteristics;
- High resistance to compression;
- Protection against corrosion;
- Prevents foaming;
- Neutral with respect to sealing materials

Efficiency

- Optimum working properties;
- Reduces wear and running noise;
- Good fluidity in cold weather, down to -36 ° C;
- Year-round use;
- Extended service life;

Application

- Universal applicability in the levers of the vehicle drive in accordance with the manufacturer's instructions;
- Cars, light and heavy trucks.
- Ideal for mixed fleets.

Waste management

Waste Oil **Wolver Universal Gear Oil 80W-90** is classified as Category 2 waste and must be disposed of in designated areas.

Compatibility

Wolver Universal Gear Oil 80W-90 is compatible with similar oils and can be mixed with any of them. In order to take full advantage of **Wolver Universal Gear Oil 80W-90**, it is recommended to use it without mixing.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	883
Viscosity at 40°C	cSt	126
Viscosity at 100°C	cSt	15
Viscosity index		122
Flash point COC	°C	234
Pour point	°C	-36