



Wolver Gleitbahnöl W 220

VERPACKUNG

208 L | 60 L | 20 L

WOLVER Gleitbahnöl W 220 are mixtures of high-quality mineral oil raffinates and special ash-free additives which prevent stick-slip effects.

Furthermore, the oils are characterized by an excellent water separation ability, very good ageing stability and outstanding corrosion protection as well as improved load-carrying capacity.

SPECIFICATIONS

ISO VG 68

MEETS THE REQUIREMENTS OF

ISO VG 68
DIN 51524-2 (HLP),
DIN 51517-3 (CLP), DIN 51502 (CGLP),
ISO 6743-13 (G),
ISO 6743/4 (HG)

Meets the requirements of
DIN 51524-2 (HLP),
DIN 51517-3 (CLP), DIN 51502 (CGLP),
ISO 6743-13 (G),
ISO 6743/4 (HG)

Application

- Excellent suitability for the lubrication of horizontal and vertical slide-ways and guideways in machine tools and other machinery, also suited for plastic-coated slideways
- Fulfill easily the requirements on the hydraulic oils according to DIN 51524-2 (HLP) and on gear oils according to DIN 51517-3 (CLP)

WOLVER Gleitbahnöl W 220 is particularly suitable for horizontal guideways with medium load conditions (i.e. in slideways and guide-ways of milling, turning and drilling machines, long-block leveller, circular and surface grinding machines). Also suitable as ash-free hydraulic oil.

Disposal

- **WOLVER Gleitbahnöl W 220** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

- **WOLVER Gleitbahnöl W 220** Compressor Oil of VG range is well-tolerated with comparable lubrications and thus can be mixed. However, it is recommendable to use only **WOLVER Gleitbahnöl W 220** compressor oil of VG-range when refilling.