



## Wolver HighTec 0W-40

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

**WOLVER HighTec SAE 0W-40** is a high-performance HC-Synthetic multigrade fuel-economy oil for diesel and petrol car engines. Specially selected HC-Synthetic base oils and highly effective long-term protective additives give this high-performance motor oil its excellent driving characteristics.

**WOLVER HighTec SAE 0W-40** with performance reserves for sporting and environmentally conscious drivers. The fuel economy leads to a reduction in CO2 emissions.

### SPECIFICATIONS:

SAE 0W-40

API SN/CF

ACEA A3/B4

### MEETS THE REQUIREMENTS OF:

BMW Longlife-01

MB 229.3

VW 502.00, 505.00

### ***Characteristics***

- High wear protection at all operating conditions
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability

### ***Effects***

- Optimum long-term protection for all engines
- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties - rapid supply of all points of lubrication
- Very good operating reliability
- Optimal engine cleanliness
- Low oil consumption
- High margin of performance and high product stability, also at extended oil change intervals
- All-year operation

- Optimal oil pressure

### **Utilization**

- High-performance and normal four-stroke petrol engines
- with multivalve-technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- with CDi-technology
- with turbo charging
- with multivalve technology
- with catalyst technology

### **Disposal**

- **WOLVER HighTec SAE 0W-40** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

- **WOLVER HighTec SAE 0W-40** is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **WOLVER HighTec SAE 0W-40**, however, the use of **WOLVER HighTec SAE 0W-40** is worth recommending.

### **Data table**

| PROPERTIES              | UNIT              | TYPICAL INDICATORS |
|-------------------------|-------------------|--------------------|
| Specific weight at 15°C | kg/m <sup>3</sup> | 851                |
| Viscosity at -30°C      | cP                | 6200               |
| Viscosity at 40°C       | cSt               | 78                 |
| Viscosity at 100°C      | cSt               | 13,6               |
| Viscosity index         |                   | 179                |
| Flash point COC         | °C                | 220                |
| Pour point              | °C                | -36                |