



Wolver HighTec 0W-40

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER HighTec SAE 0W-40 is a high-performance HC-Synthetic multigrade fuel-economy oil for diesel and petrol car engines. Specially selected HC-Synthetic base oils and highly effective long-term protective additives give this high-performance motor oil its excellent driving characteristics.

WOLVER HighTec SAE 0W-40 with performance reserves for sporting and environmentally conscious drivers. The fuel economy leads to a reduction in CO2 emissions.

SPECIFICATIONS:

SAE 0W-40

API SN/CF

ACEA A3/B4

MEETS THE REQUIREMENTS OF:

BMW Longlife-01

MB 229.3

VW 502.00, 505.00

Characteristics

- High wear protection at all operating conditions
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability

Effects

- Optimum long-term protection for all engines
- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties - rapid supply of all points of lubrication
- Very good operating reliability
- Optimal engine cleanliness
- Low oil consumption
- High margin of performance and high product stability, also at extended oil change intervals
- All-year operation

- Optimal oil pressure

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve-technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- with CDi-technology
- with turbo charging
- with multivalve technology
- with catalyst technology

Disposal

- **WOLVER HighTec SAE 0W-40** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

- **WOLVER HighTec SAE 0W-40** is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **WOLVER HighTec SAE 0W-40**, however, the use of **WOLVER HighTec SAE 0W-40** is worth recommending.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	851
Viscosity at -30°C	cP	6200
Viscosity at 40°C	cSt	78
Viscosity at 100°C	cSt	13,6
Viscosity index		179
Flash point COC	°C	220
Pour point	°C	-36