



Wolver Modelux EP2

VERPACKUNG

170 KG | 16 KG | 8 KG | 400 ML

WOLVER MODELUX EP2 - high anti-wear and extreme pressure grease. It meets the requirements of the automotive industry as a universal automotive lubricants.

WOLVER MODELUX EP2 - universal lithium grease is recommended for year-round use, as the main lubricant for automotive park and car owners in normal operating conditions.

Operating Temperature Range: -30 ° C ... + 120 ° C

SPECIFICATIONS

NLGI 2 · KP2K-30 ·
L-XCCEB 2

Characteristics

- wear protection at high loads and speeds;
- provides long-term protection against corrosion even under water, snow, dirt and dust influence;
- it provides mechanical and thermal stability;
- reliable sealing mechanism nodes.

Utilization

- Hub bearings, ball bearings, cardan shaft crosses, steering gear and other chassis components of cars and trucks;
- Accessory mechanisms for automobiles, such as windows, water pump bearings, generator bearings, cables, hinges and locks, slides, winches, etc .;
- Rolling and plain bearings, bushings, shafts, pins and other components of industrial friction, agricultural, lifting and transport, garage and power equipment under normal operating conditions.

Data table

| PROPERTIES | UNIT | TYPICAL INDICATORS |
|--------------------------|--------------------|--------------------|
| Viscosity of Oil at 40°C | mm ² /s | 152 |

| | | |
|---------------------------|----------------------|--------|
| Penetration at 25°C | 10 ⁻¹ ·mm | 275 |
| Dropping point | °C | 198 |
| Anti-corrosion properties | - | pass |
| Weld Load 4-Ball | kg | 250 |
| Colour | - | yellow |

| | | |
|-----------------|------|---------------|
| 208L - Barrel | 4039 | 4260360940392 |
| 20L - Pail | 4069 | 4260360940699 |
| 10L - Pail | 4220 | 4260360942204 |
| 400g -cartridge | 4051 | 4260360940514 |