



## Wolver Modelux EP2

### VERPACKUNG

170 KG | 16 KG | 8 KG | 400 ML

**WOLVER MODELUX EP2** - high anti-wear and extreme pressure grease. It meets the requirements of the automotive industry as a universal automotive lubricants.

**WOLVER MODELUX EP2** - universal lithium grease is recommended for year-round use, as the main lubricant for automotive park and car owners in normal operating conditions.

Operating Temperature Range: -30 ° C ... + 120 ° C

### SPECIFICATIONS

NLGI 2 · KP2K-30 ·  
L-XCCEB 2

### Characteristics

- wear protection at high loads and speeds;
- provides long-term protection against corrosion even under water, snow, dirt and dust influence;
- it provides mechanical and thermal stability;
- reliable sealing mechanism nodes.

### Utilization

- Hub bearings, ball bearings, cardan shaft crosses, steering gear and other chassis components of cars and trucks;
- Accessory mechanisms for automobiles, such as windows, water pump bearings, generator bearings, cables, hinges and locks, slides, winches, etc .;
- Rolling and plain bearings, bushings, shafts, pins and other components of industrial friction, agricultural, lifting and transport, garage and power equipment under normal operating conditions.

### Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Viscosity of Oil at 40°C	mm <sup>2</sup> /s	152

Penetration at 25°C	10 <sup>-1</sup> ·mm	275
Dropping point	°C	198
Anti-corrosion properties	-	pass
Weld Load 4-Ball	kg	250
Colour	-	yellow

208L - Barrel	4039	4260360940392
20L - Pail	4069	4260360940699
10L - Pail	4220	4260360942204
400g -cartridge	4051	4260360940514