



WOLVER Multipurpose Gear Oil GL-4 75W-90

VERPACKUNG

208 L | 60 L | 20 L | 1 L

WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90 - is a multi-purpose gear oil of viscosity category SAE 75W/90. It is based on semi synthetic ground components and a very shear stable VI-Improver which ensures at long-term the desired SAE-category acc. DIN 51512 also under highest load. Because of its excellent viscosity-temperature behaviour this product can be applied in the fleet round the year.

WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90 - is suitable for lubrication of gear boxes, differential and steering gears in vehicles where the service instructions prescribe EP gear oil types.

SPECIFICATIONS

SAE 75W-90
API GL-4
SAE 75W-90

MEETS THE REQUIREMENTS OF

MAN 341 Z-1,
MB 235.1,
ZF TE-ML 02A, 16A, 17A, 19A,
MIL-L-2105 D

Characteristics

- Very well wear protection
- First-rate oxidation stability
- High lubrication stability
- Excellent viscosity-temperature behaviour
- High pressure susceptibility
- Excellent corrosion protection
- Prevents foaming
- Neutral towards metals and sealing materials

Effects

- Optimal operating properties
- Reduces wear and background noises
- Excellent cold flow characteristics
- Free-flow up to -45°C

- All-year operation

Utilization

- Motor vehicle gear box
- Motor vehicles differential gear
- Motor vehicles steering gear
- with normal to high load according API GL 4

Disposal

WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90 gear oil is fully tolerated with comparable lubrications and can be mixed. However, it is recommended to take only **WOLVER Multipurpose Gear Oil GL-4 SAE 75W-90** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm ² /s	15.2
Viscosity index	-	146
Pour point	°C	-34
Total acid number	mgKOH/g	0.6
Flash point	°C	212
Density at 15.6 °C	kg/m ³	892

208L - Barrel 4260360942013