



## Wolver Rally Special 10W-60

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

**WOLVER Rally Special SAE 10W-60** is a HC-Synthetic engine oil for highly loaded petrol and diesel car engines.

**WOLVER Rally Special SAE 10W-60** is ideal for engines which are submitted to hardest conditions in motor sports. With its broad viscosity SAE 10W-60 extremely high temperature stability can be assured.

**WOLVER Rally Special SAE 10W-60** fulfils the high quality requirements of all car producers.

### SPECIFICATIONS:

SAE 10W-60

API SM

ACEA A3/B3

### MEETS THE REQUIREMENTS OF:

VW 501.01/505.00

MB 229.5

Porsche A40

### Characteristics

- High wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- High cleaning capability
- High oxidation and temperature stability
- Prevents black sludge formation

### Effects

- Excellent cold starting behaviour
- Very good operating reliability
- Optimises motor performance
- Optimal engine cleanliness
- Low oil consumption
- High margin of performance and high product stability
- All-year operation

### Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- CDI- and TDI motors
- Direct-injection

### **Disposal**

- **WOLVER Rally Special SAE 10W-60** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

- **WOLVER Rally Special SAE 10W60** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **WOLVER Rally Special SAE 10W-60** it is recommendable to use only **WOLVER Rally Special SAE 10W-60** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	865
Viscosity at -30°C	cP	6910
Viscosity at 40°C	cSt	184
Viscosity at 100°C	cSt	26,0
Viscosity index		177
Flash point COC	°C	222
Pour point	°C	-36
TBN	mgKOH/g	13