



Wolver STOU 10W-30, 80W

VERPACKUNG

208 L | 60 L | 20 L

WOLVER STOU SAE 10W-30, 80W - is a special oil which meets the recommendations of all well known tractor manufacturers. It can be used equally for engines, gears and hydraulic systems of modern tractors.

WOLVER STOU SAE 10W-30, 80W - high-quality basic oils and selected additives provide a disturbance-free operation of all units at all seasons. Thus also best suitable for wet brakes and clutches (power shaft clutches).

SPECIFICATIONS

SAE 10W-30, 80W API CH-4/CE/SF ACEA E3 HVLP-D 68 (ISO VG 68) API GL-4 MEETS THE REQUIREMENTS OF

ALLISON C-4
CASE MS 1118/1206/1207/1209/1230
Denison HF-2
International Harvester B6
FIAT AF 87
CASE NH MAT 3505/3509/3525/3526
CATERPILLAR TO-2
DEUTZ DQC I-02

FORD M2C48-C3/M2C-86B/M2C134-D/M2C159B,C JOHN DEERE J 27 MASSEY FERGUSON CMS 1145 (M1135-1145) MB-Freigabe 227.1/228.1 NEW HOLLAND NH 024C/030C/410B/420A ZF TE-ML 06A/B/C/F, 07B/D

Characteristics

- Reduces formation of ageing products at high temperatures
- Neutralizes acids emerging from fuel combustion
- First-rate anti-volatilization behaviour
- High ageing stability
- Excellent viscosity-temperature behaviour

Effects

- Optimal operating properties
- Provides disturbancefree operation of all engines, gears, hydraulic and brake units
- Good balanced friction behaviour at wet brakes and gears
- All-year operation
- Excellent cold starting behaviour

Utilization

• All kinds of agricultural machines

Disposal

• WOLVER STOU SAE 10W-30, 80W is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER STOU SAE 10W-30, 80W is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only **WOLVER STOU SAE 10W-30, 80W** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm²/s	11.1
Viscosity index	-	139
Pour point	°C	-34
Viscosity CCS at -25°C	mPa•s	6700
TBN	mgKOH/g	9.3
Flash point	°C	213
Density at 15.6 °C	kg/m³	876

60L - Barrel	4200	4260360942006
20L - Pail	4074	4260360940743
208L - Barrel	4045	4260360940453