



## Wolver Super Dynamic Diesel 10W-40

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 1 L

**Wolver Super Dynamic Diesel SAE 10W-40** is a semi-synthetic motor oil for all types of diesel engines with a new, improved formulation. It is based on base oils and additives that ensure engine cleanliness, economy, safety and durability.

**Wolver Super Dynamic Diesel SAE 10W-40** has excellent viscosity-temperature characteristics, which guarantees engine protection when operating in a wide temperature range and various operating conditions

**Wolver Super Dynamic Diesel SAE 10W-40** is especially effective in the diesel engines of cars and commercial vehicles of both the early years of production and modern, according to recommendations of automakers.

### SPECIFICATIONS:

SAE 10W-40

API CF

ACEA A3/B3, A3/B4

### MEETS THE REQUIREMENTS OF:

MB 229.3

VW 501.01/505.00

VOLVO VDS

MAN 271

MTU

### Characteristics

- Extreme wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

### Effects

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results

- Reduced fuel consumption
- Optimal engine cleanliness
- Low oil consumption
- All-year-round operation

### **Application**

- high-performance and normal four-stroke diesel engines
- with multivalve technology
- with catalyst technology
- with turbocharging
- without turbocharging
- CDI- HDI- and TDI-motors
- with CDi-technology
- with catalyst technology

### **Recycling**

- **WOLVER Super Dynamic Diesel SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

- **WOLVER Super Dynamic Diesel SAE 10W-40** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **WOLVER Super Dynamic Diesel SAE 10W-40** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	14.7
Viscosity index	-	150
Pour point	°C	-32
Viscosity CCS at -25 °C	mPa·s	6400
TBN	mgKOH/g	9.1
Flash point	°C	220
Density at 15.6 °C	kg/m <sup>3</sup>	866

1L - Can	4410	4260360944109
5L - Can	4412	4260360944123