



## Wolver Super Traffic 10W-40

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

**WOLVER Super Traffic 10W-40** - multigrade semisynthetic universal motor oil. Used for gas and diesel engines as well as engines operating on liquefied petroleum gas (LPG - a mixture of propane and butane), compressed natural gas (CNG - methane) turbocharged and naturally aspirated engines of passenger cars, vans and light trucks.

**WOLVER Super Traffic 10W-40** meets the requirements and oil specifications for major European, American and Asian engine manufacturers. Recommended for year-round use in various operating conditions: urban, extra-urban, start-stop mode. Ideal for mixed fleets.

**WOLVER Super Traffic 10W-40** helps to reduce engine operating clearances, leads to a reduction in oil consumption and, consequently, to a decrease the oil refilling.

SPECIFICATIONS:  
SAE 10W-40  
API API SJ / CF-4  
ACEA A3/B3, E2

MEETS THE REQUIREMENTS OF:  
MB 228.1, 229.3  
VW 502.00/505.00  
VOLVO VDS/VDS-2  
MAN M271

### **Characteristics**

- Stable viscosity and low burning oil consumption
- High resistance to aging and oxidation
- Reduces formation of aging products at high temperatures
- Excellent cold starting properties - fast supply to all lubrication points
- Excellent low temperature pumpability
- Reduced scuffing and bore polishing
- Reduces fuel consumption

### **Effects**

- German reliability
- Increase the service life of seals and gaskets, extended drain intervals
- Minimum wear at high loads to the driving parts

- Reduces the starting load on the engine
- All-year operation
- Increase operational efficiency and reduce overall costs
- Keeps stable oil film at all operating conditions
- Ensures the viscosity stability, in case the engine condition is satisfactory, when the penetration of fuel or coolant into the oil excluded

### **Application**

Universal motor oil for mixed fleets:

- Gas and diesel engines of passenger cars, light trucks and vans, as well as engines running on LPG
- Engines with dual fuel system (liquefied petroleum gas - gas, liquefied petroleum gas - diesel)
- Turbocharged
- With the catalyst
- Early year of manufacture engines, including long service life engines.

### **Recycling**

- **WOLVER Super Traffic SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER Super Traffic SAE 10W-40** is miscible with comparable lubrications. It is recommended to take only **WOLVER Super Traffic SAE 10W-40** when refilling

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	14.2
Viscosity index	-	155
Pour point	°C	-35
Viscosity CCS at -25 °C	mPa·s	5300
TBN	mgKOH/g	7.5
Flash point	°C	224
Density at 15.6 °C	kg/m <sup>3</sup>	869

1L - Can	4254	4260360942549
4L - Can	4252	4260360942525
5L - Can	4250	4260360942501
20L - Pail	4256	4260360942563
60L - Barrel	4267	4260360942679
208L - Barrel	4257	4260360942570