



Wolver Super Traffic 10W-40

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER Super Traffic 10W-40 – multigrade semisynthetic universal motor oil. Used for gas and diesel engines as well as engines operating on liquefied petroleum gas (LPG - a mixture of propane and butane), compressed natural gas (CNG - methane) turbocharged and naturally aspirated engines of passenger cars, vans and light trucks.

WOLVER Super Traffic 10W-40 meets the requirements and oil specifications for major European, American and Asian engine manufacturers. Recommended for year-round use in various operating conditions: urban, extra-urban, start-stop mode. Ideal for mixed fleets.

WOLVER Super Traffic 10W-40 helps to reduce engine operating clearances, leads to a reduction in oil consumption and, consequently, to a decrease the oil refilling.

SPECIFICATIONS

SAE 10W-40

API SJ / CF-4

ACEA A3/B3, E2

MEETS THE REQUIREMENTS OF:

MB 228.1, 229.3

VW 502.00/505.00

VOLVO VDS/VDS-2

MAN M271

Characteristics

- Stable viscosity and low burning oil consumption
- High resistance to aging and oxidation
- Reduces formation of aging products at high temperatures
- Excellent cold starting properties - fast supply to all lubrication points
- Excellent low temperature pumpability
- Reduced scuffing and bore polishing
- Reduces fuel consumption

Effects

- German reliability
- Increase the service life of seals and gaskets, extended drain intervals
- Minimum wear at high loads to the driving parts

- Reduces the starting load on the engine
- All-year operation
- Increase operational efficiency and reduce overall costs
- Keeps stable oil film at all operating conditions
- Ensures the viscosity stability, in case the engine condition is satisfactory, when the penetration of fuel or coolant into the oil excluded

Application

Universal motor oil for mixed fleets:

- Gas and diesel engines of passenger cars, light trucks and vans, as well as engines running on LPG
- Engines with dual fuel system (liquefied petroleum gas - gas, liquefied petroleum gas - diesel)
- Turbocharged
- With the catalyst
- Early year of manufacture engines, including long service life engines.

Recycling

- **WOLVER Super Traffic SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Super Traffic SAE 10W-40 is miscible with comparable lubrications. It is recommended to take only **WOLVER Super Traffic SAE 10W-40** when refilling

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	877
Viscosity at -25°C	cP	4325
Viscosity at 100°C	cSt	14,7
Viscosity index		158
Flash point COC	°C	230
Pour point	°C	-32
TBN	mgKOH/g	8,6