



Wolver Tirex HT2

VERPACKUNG

170 KG | 16 KG | 8 KG | 400 ML

WOLVER TIREX HT2 - high-premium grease based on calcium sulfonate and synthetic components.

WOLVER TIREX HT2 - used primarily at extremely high temperatures and loads. It has extremely high anti-corrosion and water-resistant properties. According to the main parameters considerably exceed the properties of lithium and complex greases.

Operating Temperature Range: -25 ° C ... + 200 ° C

SPECIFICATIONS

NLGI 2 · KP2S-25 ·
L-XBGFB 2 · LB/GC

Characteristics

- ensures efficient lubrication, high thermal and antioxidant stability and low oil separation at high temperatures;
- exceptional extreme pressure and anti-wear performance under heavy and shock loads;
- high resistance against corrosion, water and steam washout, destruction resistance under mechanical shifting forces and dirty water influence;
- increased lubrication service intervals and reducing maintenance costs.

Utilization

- Roll stands mechanisms and drive gear axis of hot rolling steel mills, continuous casting machines;
- Mechanisms and fittings for boilers, furnace and autoclaves;
- Cement, chemical and glass industries equipment, operating under high temperatures. The mechanisms and nodes of road-building machinery and heavy vehicles, vibrating screens of the asphalt plants, heavy loaded bearings in heavy industry;
- Bearings for Paper and Pulp industry equipment, bearings and equipment components used for gas concrete production, drills and hammers;
- Electric motor bearings of large dimensions.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Viscosity of Oil at 40°C	mm ² /s	456
Penetration at 25°C	10 ⁻¹ ·mm	285
Dropping point	°C	306
Anti-corrosion properties	-	pass
Weld Load 4-Ball	kg	447
Colour	-	red

400ml - cartridge	4020	4260360940200
10L- pail	4386	4260360943867
20L - pail	4237	4260360942372
208L - barel	4238	4260360942389

4260360943867