



Wolver Turbo Marine HD 40

VERPACKUNG

208 L | 60 L | 20 L

The monograde engine oil **WOLVER Turbo Marine HD 40** is based on high-quality mineral oil raffinates and new outstanding additive technologies with highest specific performance level.

High engine cleanliness, best corrosion and wear protection as well as good thermaloxidative stability were proven on the test bench and in field tests.

SPECIFICATIONS SAE 40 API CI-4 ACEA E7 MEETS THE REQUIREMENTS OF MTU Ölkategorie 2 MB-Freigabe 228.2 DETROIT DIESEL BR 2000 & 4000 MAN 270 CATERPILLAR MACK EO-M PLUS CUMMINS CES 20071, 72, 76, 77, 78

APPLICATION

- Particularly suitable for the application in middle- and high-speed diesel engines of fast ships with high and small extent of utilization, like
 - $\circ \ \ \text{fast ferries}$
 - yachts
 - patrol boats
 - o police boats
 - corvettes
 - o frigates
- Also suitable within stationary range and for diesel engines of railway vehicles
- Successful on-road tests and excellent experience in locomotives of different types

CHARACTERISTICS

- Excellent protection against wear and corrosion
- Best thermal-oxidative stability
- Good cleaning capacity
- Reduced transmission wear

ADVANTAGES AND BENEFITS

- Excellent engine cleanliness
- Long oil lifetime
- High piston cleanliness

Improved efficiency under higher number of revolutions