



Wolver Two Stroke Speed 2T

VERPACKUNG

200 L | 60 L | 1 L

Two Stroke SPEED 2-T is a modern two-stroke engine oil with synthetic basic oils and extremely effective "low smoke" two-stroke additives for universal use in combined and fresh oil lubricated air and water-cooled two-stroke gasoline engines.

Two Stroke SPEED 2-T is because of its additives excellent suitable for modern high-performance two-stroke engines of cars, motor-bikes, lawn-mowers, saw chain-driver, snowmobiles etc.

SPECIFICATIONS

API TC
JASO FC
ISO-L-EGD

MEETS THE REQUIREMENTS OF

PIAGGIO SI
HUSQVARNA 272
TISI

Characteristics

- Very well wear protection
- Excellent high temperature characteristics
- Good sticking and pressure-bursting lubrication film
- Excellent corrosion protection
- First-rate oxidation stability
- Very low ash content

Effects

- Optimal operating reliability
- Environment-friendly - no smoke formation
- Protects against deposits - spark-plug bridge formation
- Suitable for racing
- Universally usable
- Selfmixing in tank
- Selfmixing and for separate lubrication

Utilization

- Air- and watercooled two-stroke engines
- Mixing ratio up to 1:32-1:100 (Please observe service instructions)

Disposal

- **WOLVER Two Stroke SPEED 2-T** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

- **WOLVER Two Stroke SPEED 2-T** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **WOLVER Two Stroke SPEED 2-T** only.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm ² /s	8.8
Viscosity index	-	95
Pour point	°C	-29
TBN	mgKOH/g	1.34
Flash point	°C	230
Density at 15.6 °C	kg/m ³	883

1L - Can 4127 4260360941276
 208L - Barrel 4204 4260360942044