



## Wolver Ultratec A1 5W-30

### VERPACKUNG

208 L | 60 L | 20 L | 4 L | 1 L

**Wolver Ultratec A1 5W-30** – HC-synthetic multigrade low viscosity motor oil, produced by the latest technology. Specially designed for year-round use in Japanese and American passenger cars and light trucks.

**Wolver Ultratec A1 5W-30** - ideal for use in gas and diesel multi-valve engines turbocharge/ intercooler or without, where it is recommended by the manufacturer. Ideal for prolonged drain intervals and high demands of the machinery manufacturers.

**Wolver Ultratec A1 5W-30** - provides the best cleanliness of engine parts, protects from wear and reduces power losses.

### SPECIFICATIONS:

SAE 5W-30

API SN/CF

ACEA A1/B1, A5/B5 • ILSAC GF-5

### MEETS THE REQUIREMENTS OF:

FORD WSS-M2C 913-D/C/B/A

JAGUAR LAND ROVER STJLR.03.5003

### **Characteristics**

- Extreme wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Considerable wear reduction on cylinder and camshaft
- High oxydation- and thermo stability
- Low volatilization loss
- Very high cleaning capability
- Particularly low emission combustion

### **Effects**

- Reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission
- Reduced ash formation (Low SAPS)
- Light motor start
- Optimal engine cleanliness
- Very low resistance an motor starting

- Very good operating reliability
- Extended drain intervals
- All-year round operation

### **Application**

- High-performance and standard 4-stroke petrol and diesel engines with variable valve timing system
- with turbo charging
- with catalyst technology
- with extended drain interval
- with pump and nozzle engines
- with diesel particulate systems (DPF)
- with CDi-technology

### **Recycling**

**WOLVER UltraTec A1 SAE 5W-30** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER UltraTec A1 SAE 5W-30** is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **WOLVER UltraTec A1 SAE 5W-30**, however, the use of **WOLVER UltraTec A1 SAE 5W-30** is worth recommending.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	855
Viscosity at -30°C	cP	5000
Viscosity at 40°C	cSt	54
Viscosity at 100°C	cSt	9.8
Viscosity index		176
Flash point COC	°C	230
Pour point	°C	-32
TBN	mgKOH/g	6.7

1L - Blechdose4308      4260360943089

4L - Blechdose4301      4260360943010