



## Wolver UltraTec DL-1 5W-30

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

**WOLVER Ultratec DL-1 SAE 5W-30** is a state-of-the-art fully synthetic multigrade motor oil. Used for all types of gasoline and diesel engines of cars and vans. A unique technology provides maximum protection for engines of Japanese cars and others, where the specification ACEA A5/B5, C1 is required.

**WOLVER Ultratec DL-1 SAE 5W-30** ensures maximum service life for gas and diesel engines including common rail technology, catalytic converters and turbochargers, engines equipped with diesel particulate filter (DPF). It is also suitable for gas fuelled (CNG/LPG) passenger cars.

**WOLVER Ultratec DL-1 SAE 5W-30** due to the high-quality additives, oil has extremely reliable protection in all operating conditions, well pumped through the lubrication system and has pronounced energy-saving properties. Extends the working life of the engine due to a significant reduction in friction and wear, provides a reliable protection against the formation of varnish deposits and sludge.

SPECIFICATIONS:  
SAE 5W-30  
ACEA A5/B5, C1  
JASO DL-1

MEETS THE REQUIREMENTS OF:  
Mazda DPF • Mitsubishi DPF

### Characteristics

- Extreme wear protection at all operating conditions
- Excellent viscosity-temperature behaviour
- Minimum loss through friction, more power for the engine
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability
- Maximum shear stability

### Effects

- Reduces fuel consumption and exhaust emission

- Stable oil pressure
- Perfect and long-lasting engine cleanliness
- Prevents motor from incrustation
- High performance reserves and high product stability, even at longest oil change interval
- All-year operation

#### **Utilization**

- High-performance gas and diesel engines
- with multivalve technology
- with common rail technology
- with catalytic converters
- with turbocharges
- CDI- and TDI motors
- with diesel particle systems (DPF)
- CNG/LPG motors

#### **Disposal**

- **WOLVER UltraTec DL-1 SAE 5W-30** is assigned to category 2 of used oils and thus is free for disposal.

#### **Miscibility**

- **WOLVER UltraTec DL-1 SAE 5W-30** is fully compatible to customary oils and can be mixed without any doubts. However, to take full advantage of **WOLVER UltraTec DL-1 SAE 5W-30** it is recommendable to use only **WOLVER UltraTec DL-1 SAE 5W-30** when refilling.

#### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m <sup>3</sup>	851
Viscosity at -30°C	cP	6000
Viscosity at 100°C	cSt	11,20
Viscosity index		170
Flash point COC	°C	220
Pour point	°C	-32
TBN	mgKOH/g	6.0