



Wolver UltraTec Longlife 5W-30

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER UltraTec Longlife SAE 5W-30 is a newly-developed universal smooth-running multigrade motor oil based on special synthetic base oils of the latest technology. Carefully selected, highly-efficient additives give this high-performance motor oil outstanding attributes in vehicle operation.

WOLVER UltraTec Longlife SAE 5W-30 is a universal, fuel-saving, specially-composed, super-high-tech, smooth-running motor oil that exceptionally fulfils the qualities of modern petroleum and diesel engines - with and without turbo chargers - in passenger vehicles and vans, with extended oil change intervals, including particulate filters (ACEA C3). In addition, this motor oil extends the life of the particle filter.

On the basis of its special composition, **WOLVER UltraTec Longlife SAE 5W-30** is exceptionally suited for use for the newest VW 504.00/507.00 requirements, so-called VW Longlife III oils.

This high-performance engine oil can be used in other VW engines of all types, except R5, V10 TDI pump-jet engines with and without DPF diesel particulate filter, the specifications VW 503.00, 506.00, 506.01 require.

SPECIFICATIONS:
SAE 5W-30
API SN/CF/EC
ACEA C3, A3/B4

MEETS THE REQUIREMENTS OF:
MB 229.51, 229.31
VW 504.00/507.00
PORSCHE C30
BMW Longlife 04
FIAT 9.55535.S2

Characteristics

- Extrem wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Considerable wear reduction on cylinder and camshaft
- High oxydation- and thermo stability
- Low volatilization loss
- Very high cleaning capability
- Particularly low emission combustion

Effects

- Reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission
- Reduced ash build up (Low SAPS)
- Light motor running
- Optimal engine cleanliness
- Very low resistance an motor starting
- Very good operating reliability
- High margin of performance
- Extended oil change intervals
- All-year operation

Utilization

- VW and diverse new high-performance and normal four-stroke petrol engines with and without WIV systems
- with multivalve technology
- with turbo charging
- with catalyst technology
- with extended oil change interval
- VW and diverse new motor vehicle diesel engines with and without WIV systems
- with pump and nozzle engines
- with diesel particle systems(DPF)
- with CDi-technology
- with turbo charging
- with multivalve-technology
- with catalyst technology

Disposal

- **WOLVER UltraTec Longlife SAE 5W-30** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER UltraTec Longlife SAE 5W-30 is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **WOLVER UltraTec Longlife SAE 5W-30**, however, the use of **WOLVER UltraTec Longlife SAE 5W-30** is worth recommending.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	855
Viscosity at -30°C	cP	4730
Viscosity at 40°C	cSt	64,00
Viscosity at 100°C	cSt	11,50
Viscosity index		176
Flash point COC	°C	230
Pour point	°C	-45
TBN	mgKOH/g	6,7
Sulphate ashes	%	0,67